




Strut Mounted



Surface Mounted

Insert	Twist & Lock	Position Pipe	Snap In

75 Lbs. Load
(safety Factor 3)




Position	Mount w/Screw	Position Pipe	Snap In
Side grooves provide Centering guide	Counter-sunk hole allows tightening of any type of #10 fastener		

The Cush-A-Claw® Grabs on to your tube, pipe, or hose and holds it in place. The unique one piece patented design allows for quick, simple, and easy installation. It will not rust because it's molded from the same choice TPE Material of some of our other products that you've come to know and trust.

- Easy Snap-in Installation of Tube, Pipe, or Hose
- Sure Grip Strut Base Easily Rotates Into Strut
- Will Not Rust
- Non Conducting
- Saves Time and Money
- Temp Range: -50° to 275° F (-45°C to 135°C)
- Works Great Indoors or Outdoors
- Seven Sizes of Tube and Three Sizes of EMT
- Designed for Light Duty Loads and Applications
- Prevents Galvanic Corrosion of Dissimilar Metals
- An Excellent Alternative to Steel, Stainless Steel, or Galvanized Clamps.

O.D. Tube Size				EMTS Conduit Sizes			
Strut Mount Part #	Surface Mount Part #	Size		Strut Mount Part #	Surface Mount Part #	Size	
		O.D.	In.			O.D.	In.
DSACL-04	DSACLS-04	1/4"	0.250" (6mm)	DSAEMT-1/2	DSAEMTS-1/2	1/2"	0.706" (18mm)
DSACL-06	DSACLS-06	3/8"	0.375" (10mm)	DSAEMT-3/4	DSAEMTS-3/4	3/4"	0.922" (23mm)
DSACL-08	DSACLS-08	1/2"	0.500" (13mm)	DSAEMT-1	DSAEMTS-1	1"	1.163" (30mm)
DSACL-10	DSACLS-10	5/8"	0.625" (16mm)				
DSACL-12	DSACLS-12	3/4"	0.750" (19mm)				
DSACL-14	DSACLS-14	7/8"	0.875" (22mm)				
DSACL-18	DSACLS-18	1 1/8"	1.125" (29mm)				



Cush-A-Claw® is manufactured under U.S. patent #D631739, #D679177, and European Community patent #0011520030001, #0011520030002, #0011520030003, #0011520030004, #0011520030005, #0011520030006, #0011520030007

PROJECT INFORMATION:		APPROVAL STAMP:	
Project:			
Date:	Phone:		
Architect / Engineer:			
Contractor:			
Address:			
Notes 1:			